


1. Part No. Expression

P I M Q 3 2 2 5 2 0 A R 3 3 M N

(a) (b) (c) (d) (e) (f)

- | | |
|--------------------|---------------------|
| (a) Series Code | (d) Inductance Code |
| (b) Dimension Code | (e) Tolerance Code |
| (c) Material Code | (f) Special Code |


2. Configuration & Dimensions (Unit: mm)



Note: The above PCB layout reference only.

A	B	C	D	L	G	H
3.2±0.3	2.5±0.3	1.8±0.2	1.1±0.3	3.7 Ref	0.7 Ref	2.8 Ref

3. Schematic



NOTE: Specifications subject to change without notice. Please check our website for latest information.

4. General Specifications

- (a) Reliability test for this part meets AEC-Q200 standard.
- (b) Operating Temp.: - 55°C to + 150°C (including self-temperature rise)
- (c) Storage Temp.: - 55°C to + 150°C (on board)
- (d) All test data referenced to 25°C ambient.
- (e) Heat Rated Current (Irms) will cause the coil temperature rise approximately ΔT of 40°C.
- (f) Saturation Current (Isat) will cause inductance L0 to drop approximately 30%.
- (g) Rated DC Current: The lower value of Irms and Isat.
- (h) Part Temperature (Ambient + Temp. Rise): Should not exceed 150°C under worst case operating conditions.
- (i) Maximum Operating Voltage: 15V
- (j) Storage Condition (Component in its packaging)
 - i) Temperature: Less than 40°C
 - ii) Humidity: Less than 60% RH


5. Electrical Characteristics

Part Number	Inductance (μ H) @0A $\pm 20\%$	Test Frequency	Irms (A)		Isat (A)		DCR (m Ω)	
			Typ	Max	Typ	Max	Typ	Max
PIMQ322520AR33MN	0.33	1.0V/100KHz	8.5	8.0	11.0	10.0	8.0	9.6
PIMQ322520AR47MN	0.47	1.0V/100KHz	8.0	7.5	9.0	8.0	9.3	11.2
PIMQ322520AR68MN	0.68	1.0V/100KHz	7.0	6.4	8.0	7.0	13.3	16.0
PIMQ322520A1R0MN	1.00	1.0V/100KHz	6.2	5.8	7.5	6.2	18.3	22.0
PIMQ322520A1R5MN	1.50	1.0V/100KHz	5.3	4.8	6.0	5.0	25.8	31.0
PIMQ322520A2R2MN	2.20	1.0V/100KHz	3.7	3.2	5.0	4.5	38.0	46.0
PIMQ322520A3R3MN	3.30	1.0V/100KHz	3.2	2.7	4.2	3.7	56.0	65.0
PIMQ322520A4R7MN	4.70	1.0V/100KHz	2.8	2.4	3.4	2.9	90.0	98.0


NOTE: Specifications subject to change without notice. Please check our website for latest information.

6. Characteristics Curve


PIMQ322520AR33MN




PIMQ322520AR47MN




PIMQ322520AR68MN




PIMQ322520A1R0MN





PIMQ322520A1R5MN



PIMQ322520A2R2MN



NOTE: Specifications subject to change without notice. Please check our website for latest information.



NOTE: Specifications subject to change without notice. Please check our website for latest information.

7. Soldering Specification

Mildly activated rosin fluxes are preferred. Our terminations are suitable for re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

7-1. IR Soldering Reflow


Recommended temperature profiles for lead free re-flow soldering in Figure 1, Table 1.1 & 1.2 (J-STD-020E).

7-2. Iron Reflow

Products attachment with a soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended (Figure 2).


Note:

- Preheat circuit and products to 150°C.
- 355°C tip temperature (Max.)
- Never contact the ceramic with the iron tip
- 1.0mm tip diameter (Max.)
- Use a 20 watt soldering iron with tip diameter of 1.0mm
- Limit soldering time to 4~5 sec.



Reflow times: 3 times Max

Figure 1: IR Soldering Reflow



Soldering iron method: $350 \pm 5^{\circ}\text{C}$ Max

Figure 2: Iron soldering temperature profiles

NOTE: Specifications subject to change without notice. Please check our website for latest information.

Table (1.1) Reflow Profiles

Profile Type:	Pb-Free Assembly
Preheat	
-Temperature Min (T_{smin})	150°C
-Temperature Max (T_{smax})	200°C
-Time (t_s) from (T_{smin} to T_{smax})	60-120seconds
Ramp-up rate (T_L to T_p)	3°C /second max.
Liquids temperature (T_L)	217°C
Time (t_L) maintained above T_L	60-150 seconds
Classification temperature (T_c)	See Table (1.2)
Time (t_p) at $T_c - 5^\circ\text{C}$ (T_p should be equal to or less than T_c .)	* < 30 seconds
Ramp-down rate (T_p to T_L)	6°C /second max.
Time 25°C to peak temperature	8 minutes max.

T_p : maximum peak package body temperature, **T_c** : the classification temperature.

For user (customer) **T_p** should be equal to or less than **T_c** .

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

Table (1.2) Package Thickness/Volume and Classification Temperature (T_c)


	Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
PB-Free Assembly	<1.6mm	260°C	260°C	260°C
	1.6-2.5mm	260°C	250°C	245°C
	≥2.5mm	250°C	245°C	245°C

Reflow is referred to standard IPC/JEDEC J-STD-020E.

NOTE: Specifications subject to change without notice. Please check our website for latest information.


8. Packaging Information

8-1. Reel Dimension (Unit: mm)



Type	A	B	C	D
7"x8mm	8.4+1.5/-0.0	50.0 Min	13.0+5.5/-0.2	178.0±2.0

8-2. Tape Dimension (Unit: mm)




B0	A0	K0	W	P	P0
3.60±0.10	2.90±0.10	2.20±0.10	8.00±0.10	4.00±0.10	4.00±0.10
P2	E	F	T	D/D1	
2.00±0.10	1.75±0.10	3.50±0.10	0.22±0.05	1.50+0.10/-0.00	

NOTE: Specifications subject to change without notice. Please check our website for latest information.

8-3. Packaging Quantity (Unit: Pcs)

Chip/ Reel	2,000
------------	-------

8-4. Tearing Off Force



The force for tearing off cover tape is according to the follow table, in the arrow direction under the following conditions.

(Referenced ANSI/EIA-481-D-2008 of 4.11 standard)

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed (mm/min)
5~35	45~85	860~1060	300±10

Tape Size	8 mm	12 to 56 mm	72 mm or Wider
Tearing Off Force (grams)	10~100	10~130	10~150

Application Notice

1. Storage Conditions

To maintain the solderability of terminal electrodes:

- (a) Recommended products should be used within 12 months from the time of delivery.
- (b) The packaging material should be kept where no chlorine or sulfur exists in the air.

2. Transportation

- (a) Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- (b) Vacuum pick up is strongly recommended for individual components.
- (c) Bulk handling should ensure that abrasion and mechanical shock are minimized.

NOTE: Specifications subject to change without notice. Please check our website for latest information.