

1. Part No. Expression

STF07036R0YZF
(a) (b) (c) (d) (e) (f)

- (a) Series Code


(b) Dimension Code

(c) Inductance Code
- (d) Tolerance Code

(e) Special Code

(f) Packaging Code

2. Configuration & Dimensions (Unit: mm)




Note: The above PCB layout reference only.


A	B	C	D	E	G	H	I
8.00±0.20	5.30±0.20	3.50 Max	5.80±0.20	2.54±0.30	5.00 Ref	1.50 Ref	1.80 Ref

NOTE: Specifications subject to change without notice. Please check our website for latest information.

3. Schematic



4. Material List



- (a) Core
- (b) Wire
- (c) Base
- (d) Cover
- (e) Adhesive
- (f) Ink

5. General Specifications

- (a) Operating Temp.: - 40°C to +125°C (including self-temperature rise)
- (b) Resistance to solder heat: 260°C. 10secs
- (c) Heat Rated Current (Irms) will cause the coil temperature rise ΔT of 45°C Max.
- (d) Storage Condition (Component in its packaging)
 - i) Temperature: -10°C to 40°C
 - ii) Humidity: Less than 60% RH

NOTE: Specifications subject to change without notice. Please check our website for latest information.


6. Electrical Characteristics

Part Number	Inductance L1, L2 (μ H) $\pm 40\%$	DCR N1, N2 (Ω) Max	Rated Current (A)	Impedance (Ω) Min	Frequency Range (MHz)
STF07036R0YZF	6.0	0.040	2.00	90	30~500
STF0703250YZF	25.0	0.070	1.60	300	20~200
STF0703550YZF	55.0	0.130	1.10	500	6~80
STF0703101YZF	100.0	0.220	0.90	600	4~40
STF0703151YZF	150.0	0.420	0.65	900	3~30


Note:

Hi-Pot Test (N1-N2): 500VAC 60Hz 3mA 1 Minute

7. Characteristics Curve



Measuring Circuit :



RF Impedance Analyzer

NOTE: Specifications subject to change without notice. Please check our website for latest information.

8. Soldering Specification

Mildly activated rosin fluxes are preferred. Our terminations are suitable for re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

8-1. IR Soldering Reflow


Recommended temperature profiles for lead free re-flow soldering in Figure 1, Table 1.1 & 1.2 (J-STD-020E).

8-2. Iron Reflow

Products attachment with a soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended (Figure 2).


Note:

- (a) Preheat circuit and products to 150°C.
- (b) 355°C tip temperature (Max.)
- (c) Never contact the ceramic with the iron tip
- (d) 1.0mm tip diameter (Max.)
- (e) Use a 20-watt soldering iron with tip diameter of 1.0mm
- (f) Limit soldering time to 4~5 sec.



Reflow times: 3 times Max

Figure 1: IR Soldering Reflow



Soldering iron method: 350±5°C Max

Figure 2: Iron soldering temperature profiles

NOTE: Specifications subject to change without notice. Please check our website for latest information.

Table (1.1) Reflow Profiles

Profile Type:	Pb-Free Assembly
Preheat	
-Temperature Min (T_{smin})	150°C
-Temperature Max (T_{smax})	200°C
-Time (t_s) from (T_{smin} to T_{smax})	60-120seconds
Ramp-up rate (T_L to T_p)	3°C /second max.
Liquids temperature (T_L)	217°C
Time (t_L) maintained above T_L	60-150 seconds
Classification temperature (T_c)	See Table (1.2)
Time (t_p) at $T_c - 5^\circ\text{C}$ (T_p should be equal to or less than T_c .)	* < 30 seconds
Ramp-down rate (T_p to T_L)	6°C /second max.
Time 25°C to peak temperature	8 minutes max.

T_p: maximum peak package body temperature, **T_c**: the classification temperature.

For user (customer) **T_p** should be equal to or less than **T_c**.

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

Table (1.2) Package Thickness/Volume and Classification Temperature (T_c)


	Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
PB-Free Assembly	<1.6mm	260°C	260°C	260°C
	1.6-2.5mm	260°C	250°C	245°C
	≥2.5mm	250°C	245°C	245°C

Reflow is referred to standard IPC/JEDEC J-STD-020E.

NOTE: Specifications subject to change without notice. Please check our website for latest information.


9. Packaging Information

9-1. Reel Dimension (Unit: mm)



Type	A	B	C	D	E	G	N	T
13"x16mm	330.0	21.0±0.8	13.0 Ref	16.0	2.0 Ref	18.0 Max	50.0 Min	22.4

9-2. Tape Dimension (Unit: mm)




9-3. Packaging Quantity (Unit: Pcs)

Inner/Reel			Outer Carton		
QTY(PCS)	G.W.(gw)	STYLE	QTY(PCS)	G.W.(Kg)	STYLE(cm)
1500	1200	13-16	9000	10.7	40x40x24

NOTE: Specifications subject to change without notice. Please check our website for latest information.

9-4. Tearing Off Force



The force for tearing off cover tape is according to the follow table, in the arrow direction under the following conditions.

(Referenced ANSI/EIA-481-D-2008 of 4.11 standard)

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed (mm/min)
5~35	45~85	860~1060	300±10

Tape Size	8 mm	12 to 56 mm	72 mm or Wider
Tearing Off Force (grams)	10~100	10~130	10~150

Application Notice

1. Storage Conditions

To maintain the solderability of terminal electrodes:

- (a) Recommended products should be used within 12 months from the time of delivery.
- (b) The packaging material should be kept where no chlorine or sulfur exists in the air.

2. Transportation

- (a) Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- (b) Vacuum pick up is strongly recommended for individual components.
- (c) Bulk handling should ensure that abrasion and mechanical shock are minimized.

NOTE: Specifications subject to change without notice. Please check our website for latest information.