


1. Part No. Expression

STX555504100KMPA2

(a) (b) (c) (d) (e)

- | | |
|---------------------|--------------------|
| (a) Series Code | (d) Tolerance Code |
| (b) Dimension Code | (e) Internal Code |
| (c) Inductance Code | |

2. Configuration & Dimensions (Unit: mm)



A	B	C	D	E
55.0±1.0	55.0±1.0	5.0 Ref	47.0 Ref	4.5 Max

NOTE: Specifications subject to change without notice. Please check our website for latest information.

3. Schematic:




4. Electrical Characteristics

Inductance (μH) $\pm 10\%$	Test Frequency	DCR ($\text{m}\Omega$) Max	I _{rms} (mA) Max
10	1V/100KHz	80	6000

5. General Specification

- (a) Operating Temp.: -40°C to $+85^{\circ}\text{C}$
- (b) Storage Temp.: -40°C to $+85^{\circ}\text{C}$ (Packaging)
- (c) Heat Rated Current (I_{rms}) will cause the coil temperature rise ΔT of 40°C Max.
- (d) Power Rating: 15W
- (e) Compatible to Qi standard MP-A2 design.

6. Material List



- (a) Ferrite Sheet (MnZn)
- (b) Adhesive
- (c) Wire

NOTE: Specifications subject to change without notice. Please check our website for latest information.